

OHAYO BATTERY

TYPE	AH RATE	LAYOUT	PLATES	DIMENSIONS			
				L	W	H	TH
J I S For Japanese Vehicles							
12N24-3/4	26	+ - / - +	9	18.7	12.7	16.2	18.4
NS40ZL	35	- +	11	19.7	12.9	20.3	22.7
N40	40	+ -	11	23.8	12.9	20.3	22.7
N50	50	+ -	9	26.0	17.3	20.4	22.5
N50Z	60	+ -	11	26.0	17.3	20.4	22.5
NS70	65	+ -	13	26.0	17.3	20.4	22.5
N70	70	+ -	13	30.6	17.3	20.4	22.5
NX-120-7	80	+ -	17	30.6	17.3	20.4	22.5
N100	100	+ -	17	41.0	17.6	21.3	23.4
N120	120	+ -	21	50.5	18.5	21.3	25.7
N150	150	+ -	27	50.8	22.2	21.3	25.7
N200	200	+ -	37	52.1	27.8	22.0	27.0
D I N For European Vehicles							
544-59	44	- +	9	22.1	17.5	19.0	19.0
555-59	55	- +	11	24.6	17.5	19.0	19.0
566-38	66	- +	13	30.6	17.5	19.0	19.0
588-27	88	- +	17	38.1	17.5	19.0	19.0
DEEP CYCLE For APS / UPS							
N100 T	100	+ -	19	41.0	17.6	21.3	23.4
N150 T	150	+ -	29	50.8	22.2	21.3	25.7
N200 T	200	+ -	39	52.1	27.8	22.0	27.0